



Cinelite 2000W

LAMPHEAD CONTENTS

- Lamp Housing without Bulb (purple grey color)
- 4-leaf Rotatable Barndoor with Safety Wire
- Wire Guard
- Stirrup with Ø16mm (5/8 in.) Socket
- Inlet Cable 3m (10 ft.)
- In-Line Switch

Requires Lamp Bulb

Cinelite 2000W

SPECIFICATIONS

Identity No.	L02000TO	
Capacity	2,000W	
Voltage	240V or 120V	
Lamp Type	P2/27 2000W 230V or FEY 2000W 120V	
Color Temp.	3200K	
Lamp Holder	RX7s	
Stirrup	Ø16mm (5/8 in.) Socket	
Class	1	
Max. Surface Temp.	220 °C	(428 °F)
Max. Ambient Temp.	45 °C	(113 °F)
Min. Distance to Illuminated Object	2 m	(6.5 ft)
Min. Distance to Flammable Object	1 m	(3.2 ft)
Operating Range	+45° ~ 0° ~ -45°	
Weight (Lamphead)	3.5 kg	(7.7 lbs)

ACCESSORIES

4-leaf Rotatable Barndoor


Set of 4 Scrims Ø254mm(10 in.):

Full Single, Full Double, Half Single, Half Double

Scrim Bag

Safety Wire (for Barndoor)

PHOTOMETRIC DATA



	2m (7ft)	4m (14ft)	6m (20ft)
Spot [24°]			
Lux	33080	8270	3676
Beam Ø	0.85m (3ft)	1.70m (6ft)	2.55m (9 ft)
Flood [79°]			
Lux	6310	1578	701
Beam Ø	3.30m (11 ft)	6.59m (22 ft)	9.89m (33 ft)

DIMENSIONS (in)

