



Cinelite 650W

LAMPHEAD CONTENTS

- Lamp Housing without Bulb (purple grey color)
- 4-leaf Rotatable Barndoor with Safety Wire
- Wire Guard
- Stirrup with Ø16mm (5/8 in.) Socket
- Inlet Cable 3m (10 ft.)
- In-Line Switch
- Accessory Holder

Requires Lamp Bulb

Cinelite 650W

SPECIFICATIONS

| | |
|-------------------------------------|--|
| Identity No. | L00650TD |
| | L0065ATO (with Accessory Holder) |
| Capacity | 650W / 600W / 500W |
| Voltage | 240V or 120V or 100V |
| Lamp Type | DYR650W 230V or DYS600W 120V or JCD500WCC 100V |
| Color Temp. | 3200K |
| Lamp Holder | GY9.5 |
| Stirrup | Ø16mm (5/8 in.) Socket |
| Class | 1 |
| Max. Surface Temp. | 220 °C (428 °F) |
| Max. Ambient Temp. | 45 °C (113 °F) |
| Min. Distance to Illuminated Object | 1 m (3.2 ft) |
| Min. Distance to Flammable Object | 0.1 m (.32 ft) |
| Operating Range | +45° ~ 0° ~ -45° |
| Weight (Lamphead) | 1.5 kg (3.3 lbs) |

ACCESSORIES

4-leaf Rotatable Barndoor

Set of 4 Scrims Ø127mm :


Full Single, Full Double, Half Single, Half Double

Scrim Bag

Safety Wire (for Barndoor)

Accessory Holder

PHOTOMETRIC DATA



| | 2m (7ft) | 4m (14ft) | 6m (20ft) |
|--------------|----------------|-----------------|-----------------|
| Spot (27.4°) | | | |
| Lux | 3172 | 793 | 352 |
| Beam Ø | 0.97m (3ft) | 1.95m (7ft) | 2.93m (10ft) |
| Flood (59°) | | | |
| Lux | 1428 | 357 | 159 |
| Beam Ø | 2.27m (8ft) | 4.53m (15ft) | 6.80m (24ft) |

DIMENSIONS (in)

