



Daylight Fresnel 9kW/6kW SE

LAMPHEAD CONTENTS

- Lamp Housing without Bulb (purple grey & silver color)
- 4-leaf Rotatable Barndoor with Safety Wire
- Ø450mm (17-3/4 in.) Fresnel Lens
- Inlet Cable with Multi-Pin Connector
- Stirrup with Ø28mm (1-1/8 in.) Spigot

Requires Electronic Ballast, Lamphead to Ballast Cable and Lamp Bulb

Daylight Fresnel 9kW/6kW SE

SPECIFICATIONS

Identify No.	L09060DS
Capacity	9,000W / 6,000W
Lamp Bulb Voltage	160V / 125V
Fresnel Lens	Ø450mm (17-3/4 in.)
Lamp Type	CSR 9000/SE/HR or HMI 9000W/SE MSR 6000/HR or HMI 6000W/SE
Color Temp.	5600K
Lamp Holder	GX38
Stirrup	Ø28mm (1-1/8 in.) Spigot
Class / IP Rating	1 / IP 23
Max. Surface Temp.	220 °C / 200 °C - 428 °F / 392 °F
Max. Ambient Temp.	45 °C (113 °F)
Min. Distance to Illuminated Object	(9k) 15m - 12m / (6k) 49ft - 39ft
Min. Distance to Flammable Object	1.5 m (4.9 ft)
Operating Range	+45° ~ 0° ~ -45°
Weight (lamphead)	38.7 kg (85.3 lbs)
Weight (with barndoor)	43.7 kg (96.3 lbs)

ACCESSORIES

Electronic Ballast V3 : 9kW/6kW

Lamphead to Ballast Cable : 7m (23 ft.) or 15m (49 ft.)

4-leaf Rotatable Barndoor

Filter Frame

Set of 4 Scrims Ø533mm (21 in.) :


Full Single, Full Double, Half Single, Half Double

Scrim Bag

Safety Cable (for lamphead)

Safety Wire (for barndoor)

PHOTOMETRIC DATA



9000W

Spot (6°)			
Lux	94000	33000	17000
Beam Ø	0.84m (2.7ft)	1.47m (4.8ft)	2.10m (6.9ft)
Flood (65°)			
Lux	6000	2000	1080
Beam Ø	10.19m (33.4ft)	17.84m (58.5ft)	25.48m (83.6ft)



6000W

Spot (6°)			
Lux	59653	19479	9545
Beam Ø	0.84m (2.7ft)	1.47m (4.8ft)	2.10m (6.9ft)
Flood (65°)			
Lux	4498	1469	720
Beam Ø	10.19m (33.4ft)	17.84m (58.5ft)	25.48m (83.6ft)

DIMENSIONS (in)

