

# ELECTRONIC BALLAST V3

1.8kW/1.2kW/575W  
[Multi-Voltage]



**1.8kW/1.2kW/575W V3 [Multi-Voltage,1000Hz]**

■ SPECIFICATIONS

Identity No.	B518PEK3 (1000Hz, DMX) B518PNK3 (1000Hz)
Max. Power	1,980VA
Input Voltage	90 - 125V AC 180 - 250V AC
Input Current	11 - 8A @ 180 - 250V AC 22 - 16A @ 90 - 125V AC
Frequency	50Hz or 60Hz
Output Mode	60Hz (Silent) 75Hz (Flicker Free) 1000Hz (High Speed)
Power Factor	0.98 (PFC)
Efficiency	91% (PFC)
Dimming Control	55%
Fusing	25A
No-load Voltage	360V
Max. Ambient Temp.	50 °C [122 °F]
Class / IP Rating	1 / IP 22
Weight	9.5 kg [20.9 lbs]

**1.8kW/1.2kW/575W V3 [Multi-Voltage,300Hz]**

■ SPECIFICATIONS

Identity No.	B518PEX3 (300Hz, DMX) B518PNX3 (300Hz)
Max. Power	1,980VA
Input Voltage	90 - 125V AC 180 - 250V AC
Input Current	11 - 8A @ 180 - 250V AC 22 - 16A @ 90 - 125V AC
Frequency	50Hz or 60Hz
Output Mode	60Hz (Silent) 75Hz (Flicker Free) 300Hz (High Speed)
Power Factor	0.98(PFC)
Efficiency	91%(PFC)
Dimming Control	55%
Fusing	25A
No-load Voltage	360V
Max. Ambient Temp.	50 °C [122 °F]
Class / IP Rating	1 / IP 22
Weight	9.5 kg [20.9 lbs]

■ DIMENSIONS [in]

