

# ELECTRONIC BALLAST V3

## 800W/575W [Multi-Voltage]



### 800W/575W V3 [Multi-Voltage,1000Hz]

■ SPECIFICATIONS

Identity No.	B008PEK3 (1000Hz, DMX) B008PNK3 (1000Hz)
Max. Power	880VA
Input Voltage	90 - 125V AC 180 - 250V AC
Input Current	5 - 4A @ 180 - 250V AC 10 - 7A @ 90 - 125V AC
Frequency	50Hz or 60Hz
Output Mode	60Hz (Silent) 75Hz (Flicker Free) 1000Hz (High Speed)
Power Factor	0.98 (PFC)
Efficiency	87% (PFC)
Dimming Control	55%
Fusing	25A
No-load Voltage	360V
Max. Ambient Temp.	50 °C [122 °F]
Class / IP Rating	1 / IP 22
Weight	7.4 kg [16.3 lbs]

### 800W/575W V3 [Multi-Voltage,300Hz]

■ SPECIFICATIONS

Identity No.	B008PEX3 (300Hz, DMX) B008PNX3 (300Hz)
Max. Power	880VA
Input Voltage	90 - 125V AC 180 - 250V AC
Input Current	5 - 4A @ 180 - 250V AC 10 - 7A @ 90 - 125V AC
Frequency	50Hz or 60Hz
Output Mode	60Hz (Silent) 75Hz (Flicker Free) 300Hz (High Speed)
Power Factor	0.98 (PFC)
Efficiency	87% (PFC)
Dimming Control	55%
Fusing	25A
No-load Voltage	360V
Max. Ambient Temp.	50 °C [122 °F]
Class / IP Rating	1 / IP 22
Weight	7.4 kg [16.3 lbs]

■ DIMENSIONS [in]

