



Maxibrute 6

■ LAMPHEAD CONTENTS

- Lamp Housing without Bulb # (black color)
- Wire Guard
- Stirrup with Ø28mm(1-1/8 in.) Spigot

Requires Lamp Bulb

Maxibrute 6

■ SPECIFICATIONS

Identity No.	L06001COMXB(220V)
	L061S1COMXB(220V)
	L06001C1MXB(110V)
	L061S1C1MXB(110V)
Capacity	6,000W
Voltage	220 - 240V AC or 110 - 120V AC
Lamp Type	Par64 1000W 120V/240V
Color Temp.	5000K / 3200K
Lamp Holder	GX16d
Stirrup	Ø28mm(1-1/8 in.) Spigot
Class	1
Max. Surface Temp.	200 °C (392 °F)
Max. Ambient Temp.	45 °C (113 °F)
Min. Distance to Illuminated Object	5 m (16.4 ft)
Min. Distance to Flammable Object	1.5 m (4.9 ft)
Operating Range	+45° ~ 0° ~ -45°
Weight (Lamphead)	18.8 kg (41.4 lbs)

■ ACCESSORIES

2-leaf Barndoor

Safety Wire (for barndoor)

Filter Frame Outrigger

Studio Dolly

■ INPUT PANEL

L06001COMXB, L06001C1MXB :

1 x CEE 32A 2P+E

L061S1COMXB, L061S1C1MXB :

1 x Socapex, 1 x CEE 32A 2P+E

■ DIMENSIONS (in)

