



## Daylight Power Beam 1.8kW/1.2kW

### LAMPHEAD CONTENTS

- Lamp Housing without Bulb (purple grey & silver color)
- High Reflective Parabolic Glass Mirror
- Inlet Cable with Multi-Pin Connector
- Stirrup with Ø28mm (1-1/8 in.) Spigot





# Requires Electronic Ballast,  
Lamphead to Ballast Cable and Lamp Bulb

## Daylight Power Beam 1.8kW/1.2kW

### SPECIFICATIONS

Identify No.	L01812DPB	
Capacity	1,800W / 1,200W	
Lamp Bulb Voltage	140V / 100V	
Parabolic Reflector	Ø498mm	[19.6 in.]
UV Protective Lens	Ø500mm	[19.7 in.]
Lamp Type	HMI 1800W/SE or HMI 1200W/SE	
Color Temp.	5600K	
Lamp Holder	G38	
Stirrup	with Ø28mm (1-1/8 in.) Spigot	
Class / IP Rating	1 / IP 23	
Max. Surface Temp.	160 °C	[356 °F]
Max. Ambient Temp.	45 °C	[113 °F]
Min. Distance to Illuminated Object	6.75m / 5m	[22.1ft / 16.4ft]
Min. Distance to Flammable Object	1.2m	[3.9 ft]
Operating Range	+45° ~ 0° ~ -45°	
Weight (lamphead)	38kg	[83.8 lbs]

### ACCESSORIES



### PHOTOMETRIC DATA

		7m (23ft)	20m (66ft)	35m (115ft)	50m (164ft)	75m (264ft)
1.8kW	Spot	Lux 253061	31000	10122	4960	2204
	Beam Ø	0.49m (1.6ft)	0.49m (1.6ft)	0.49m (1.6ft)	0.49m (1.6ft)	0.49m (1.6ft)
1.8kW	Flood	Lux 17270	2116	691	338	150
	Beam Ø	1.84m (6ft)	5.27m (17.3ft)	9.22m (30.2ft)	13.17m (43.2ft)	19.75m (64.8ft)
1.2kW	Spot	Lux 164898	20200	6596	3232	1436
	Beam Ø	0.49m (1.6ft)	0.49m (1.6ft)	0.49m (1.6ft)	0.49m (1.6ft)	0.49m (1.6ft)
1.2kW	Flood	Lux 10765	1319	431	210	94
	Beam Ø	1.84m (6ft)	5.27m (17.3ft)	9.22m (30.2ft)	13.17m (43.2ft)	19.75m (64.8ft)

### DIMENSIONS (in)

