



Daylight Power Beam 9kW/6kW

LAMPHEAD CONTENTS

- Lamp Housing without Bulb (purple grey & silver color)
- High Reflective Parabolic Glass Mirror
- Inlet Cable with Multi-Pin Connector
- Stirrup with Ø28mm (1-1/8 in.) Spigot




Requires Electronic Ballast, Lamphead to Ballast Cable and Lamp Bulb

Daylight Power Beam 9kW/6kW

SPECIFICATIONS

Identify No.	L09060DPB	
Capacity	9,000W / 6,000W	
Lamp Bulb Voltage	160V / 125V	
Parabolic Reflector	Ø628mm	[24.7in]
UV Protective Lens	Ø645mm	[25.4in]
Lamp Type	CSR 9000W/SE/HR or HMI 9000W/SE or HMI 6000W/SE	
Color Temp.	5600K	
Lamp Holder	GX38	
Stirrup	with Ø28mm (1-1/8 in.) Spigot	
Class / IP Rating	1 / IP 23	
Max. Surface Temp.	220 °C	[428 °F]
Max. Ambient Temp.	45 °C	[113 °F]
Min. Distance to Illuminated Object	18m / 16.5m	[59ft / 54ft]
Min. Distance to Flammable Object	1.5m	[4.9ft]
Operating Range	+45° ~ 0° ~ -45°	
Weight (lamphead)	57kg	[125.7lbs]

ACCESSORIES



PHOTOMETRIC DATA

		15m (49ft)	25m (82ft)	50m (164ft)	75m (246ft)	100m (328ft)
9kW	Lux	190000	68400	17100	7600	4275
	Spot Beam Ø	0.61m (2ft)	0.61m (2ft)	0.61m (2ft)	0.61m (2ft)	0.61m (2ft)
Flood	Lux	19111	6880	1720	764	430
	Flood Beam Ø	3.6m (11.8ft)	6.00m (19.7ft)	12.01m (39.4ft)	18.01m (59.1ft)	24.02m (78.8ft)
6kW	Lux	147217	53000	13250	5889	3312
	Spot Beam Ø	0.61m (2ft)	0.61m (2ft)	0.61m (2ft)	0.61m (2ft)	0.61m (2ft)
Flood	Lux	15111	5440	1360	604	340
	Flood Beam Ø	3.6m (11.8ft)	6.00m (19.7ft)	12.01m (39.4ft)	18.01m (59.1ft)	24.02m (78.8ft)

DIMENSIONS (in)

