

ELECTRONIC BALLAST V3

2500W
(Multi-Voltage)



2500W V3 (Multi-Voltage, 1000Hz)

■ SPECIFICATIONS

Identity No.	B025PEK3 (1000Hz, DMX) B025PNK3 (1000Hz)
Max. Power	2,750VA
Input Voltage	90 - 125V AC 180 - 250V AC
Input Current	15 - 11A @ 180 - 250V AC 31 - 22A @ 90 - 125V AC
Frequency	50Hz or 60Hz
Output Mode	60Hz (Silent) 75Hz (Flicker Free) 1000Hz (High Speed)
Power Factor	0.99 (PFC)
Efficiency	91% (PFC)
Dimming Control	55%
Fusing	50A
No-load Voltage	360V
Max. Ambient Temp.	50 °C
Class / IP Rating	1 / IP 22
Weight	14.0 kg (30.9 lbs)

2500W V3 (Multi-Voltage, 300Hz)

■ SPECIFICATIONS

Identity No.	B025PEX3 (300Hz, DMX) B025PNX3 (300Hz)
Max. Power	2,750VA
Input Voltage	90 - 125V AC 180 - 250V AC
Input Current	15 - 11A @ 180 - 250V AC 31 - 22A @ 90 - 125V AC
Frequency	50Hz or 60Hz
Output Mode	60Hz (Silent) 75Hz (Flicker Free) 300Hz (High Speed)
Power Factor	0.99 (PFC)
Efficiency	91% (PFC)
Dimming Control	55%
Fusing	50A
No-load Voltage	360V
Max. Ambient Temp.	50 °C
Class / IP Rating	1 / IP 22
Weight	14.0 kg (30.9 lbs)

■ DIMENSIONS (mm)

