

ELECTRONIC BALLAST V3

4kW/2.5kW (Multi-Voltage)



4kW/2.5kW V3 (Multi-Voltage, 1000Hz)

■ SPECIFICATIONS

Identity No.	B042PDK3 (1000Hz, DMX) B042PNK3 (1000Hz)
Max. Power	4,400VA
Input Voltage	90 - 125V AC 180 - 250V AC
Input Current	24 - 18A @ 180 - 250V AC 49 - 35A @ 90 - 125V AC
Frequency	50Hz or 60Hz
Output Mode	60Hz (Silent) 75Hz (Flicker Free) 1000Hz (High Speed)
Power Factor	0.99 (PFC)
Efficiency	91% (PFC)
Dimming Control	55%
Fusing	100A
No-load Voltage	360V
Max. Ambient Temp.	50 °C [122 °F]
Class / IP Rating	1 / IP 22
Weight	21.7 kg [47.8 lbs]

4kW/2.5kW V3 (Multi-Voltage, 300Hz)

■ SPECIFICATIONS

Identity No.	B042PDX3 (300Hz, DMX) B042PNX3 (300Hz)
Max. Power	4,400VA
Input Voltage	90 - 125V AC 180 - 250V AC
Input Current	24 - 18A @ 180 - 250V AC 49 - 35A @ 90 - 125V AC
Frequency	50Hz or 60Hz
Output Mode	60Hz (Silent) 75Hz (Flicker Free) 300Hz (High Speed)
Power Factor	0.99 (PFC)
Efficiency	91% (PFC)
Dimming Control	55%
Fusing	100A
No-load Voltage	360V
Max. Ambient Temp.	50 °C [122 °F]
Class / IP Rating	1 / IP 22
Weight	21.7 kg [47.8 lbs]

■ DIMENSIONS (in)

