



## Cinelite 1000W

### LAMPHEAD CONTENTS

- Lamp Housing without Bulb (purple grey color)
- 4-leaf Rotatable Barndoor with Safety Wire
- Wire Guard
- Stirrup with Ø16mm (5/8 in.) Socket
- Inlet Cable 3m (10 ft.)
- In-Line Switch
- Accessory Holder

# Requires Lamp Bulb

## Cinelite 1000W

### SPECIFICATIONS

Identity No.	L01000TD
	L0100ATD (with Accessory Holder)
Capacity	1,000W
Voltage	240V or 120V
Lamp Type	P2/35 1000W 230V or DXW 1000W 120V
Color Temp.	3200K
Lamp Holder	R7s
Stirrup	Ø16mm (5/8 in.) Socket
Class	1
Max. Surface Temp.	220 °C (428 °F)
Max. Ambient Temp.	45 °C (113 °F)
Min. Distance to Illuminated Object	1.5 m (5 ft)
Min. Distance to Flammable Object	0.5 m (1.6 ft)
Operating Range	+45° ~ 0° ~ -45°
Weight (Lamphead)	1.5 kg (3.3 lbs)

### ACCESSORIES

#### 4-leaf Rotatable Barndoor

Set of 4 Scrims Ø191mm (7-1/2 in.) :

Full Single, Full Double, Half Single, Half Double

Scrim Bag

Safety Wire (for Barndoor)

Accessory Holder

### PHOTOMETRIC DATA



	2m (7ft)	4m (14ft)	6m (20ft)
Spot (40°)			
Lux	9292	2323	1032
Beam Ø	1.46m (5ft)	2.91m (10ft)	4.37m (15ft)
Flood (89°)			
Lux	2929	732	325
Beam Ø	3.93m (13ft)	7.86m (26ft)	11.79m (39ft)

### DIMENSIONS (in)

