



Tungsten Power Beam 5kW/2kW

LAMPHEAD CONTENTS




- Lamp Housing without Bulb (purple grey & silver color)
- High Reflective Parabolic Glass Mirror
- On-Off Switch
- Inlet Cable 1.5m (Bare End) #
- Stirrup with Ø28mm (1-1/8 in.) Spigot

Tungsten Power Beam 5kW/2kW

SPECIFICATIONS

Identify No.	L05020TPB (220V)
Capacity	5,000W / 2,000W
Voltage	200 - 240V AC
Parabolic Reflector	Ø498mm (19.6 in)
Protective Lens	Ø500mm (19.7 in)
Lamp Type	5000W SE
Color Temp.	3200K
Lamp Holder	G38
Stirrup	w/ Ø28mm (1-1/8 in.) Spigot
Class / IP Rating	1 / IP 23
Max. Surface Temp.	210 °C (410 °F)
Max. Ambient Temp.	45 °C (113 °F)
Min. Distance to Illuminated Object	5m (16.4 ft)
Min. Distance to Flammable Object	1.5m (4.9 ft)
Operating Range	+45° ~ 0° ~ -45°
Weight (lamphead)	33kg (73 lbs)

ACCESSORIES



PHOTOMETRIC DATA

		7.5m (25ft)	20m (66ft)	35m (115ft)	50m (164ft)
5kW	Lux	32000	4500	1469	720
	Spot Beam Ø	1.28m (4.2ft)	3.4m (11.4ft)	5.95m (19.5ft)	8.5m (27.9ft)
Flood	Lux	3653	514	168	82
	Flood Beam Ø	3.38m (11.1ft)	9m (29.5ft)	15.75m (51.7ft)	22.5m (73.8ft)
2kW	Lux	35556	5000	1633	800
	Spot Beam Ø	0.83m (2.7ft)	2.2m (7.2ft)	3.85m (12.6ft)	5.5m (18ft)
Flood	Lux	1557	219	72	35
	Flood Beam Ø	3.38m (11.1ft)	9m (29.5ft)	15.75m (51.7ft)	22.5m (73.8ft)

DIMENSIONS (in)

