

ELECTRONIC BALLAST V3

1.2kW/575W [Multi-Voltage]



[1000Hz]

[300Hz]

1.2kW/575W V3 [Multi-Voltage,1000Hz]

■ SPECIFICATIONS

Identity No.	B015PEK3 (1000Hz, DMX) B015PNK3 (1000Hz)
Max. Power	1,320VA
Input Voltage	90 - 125V AC 180 - 250V AC
Input Current	7 - 5A @ 180 - 250V AC 15 - 11A @ 90 - 125V AC
Frequency	50Hz or 60Hz
Output Mode	60Hz (Silent) 75Hz (Flicker Free) 1000Hz (High Speed)
Power Factor	0.98 (PFC)
Efficiency	91% (PFC)
Dimming Control	55%
Fusing	25A
No-load Voltage	360V
Max. Ambient Temp.	50 °C [122 °F]
Class / IP Rating	1 / IP 22
Weight	7.4 kg [16.5 lbs]

1.2kW/575W V3 [Multi-Voltage,300Hz]

■ SPECIFICATIONS

Identity No.	B015PEX3 (300Hz, DMX) B015PNX3 (300Hz)
Max. Power	1,320VA
Input Voltage	90 - 125V AC 180 - 250V AC
Input Current	7 - 5A @ 180 - 250V AC 15 - 11A @ 90 - 125V AC
Frequency	50Hz or 60Hz
Output Mode	60Hz (Silent) 75Hz (Flicker Free) 300Hz (High Speed)
Power Factor	0.98 (PFC)
Efficiency	91% (PFC)
Dimming Control	55%
Fusing	25A
No-load Voltage	360V
Max. Ambient Temp.	50 °C [122 °F]
Class / IP Rating	1 / IP 22
Weight	7.4 kg [16.5 lbs]

■ DIMENSIONS [in]

